

Registro pile ed accumulatori IT18060P00004828 Registro nazionale RAEE IT18090000010777 Iscrizione FER Rinnovabili









ISO9001

ISO45001


ISO14001

SA8000

Intelligent PDU



- Enables reliable load distribution
- Real-time measurement of individual loads (A)
- Measurement of total active power
- Possibility to schedule the shutdown of individual loads
- Configurable startup delay for each load to prevent current spikes
- Communication via serial interface, with SNMP and USB interoperability
- Easily integrable into high-end supervision systems
- Large LCD display for easy reading of statuses and key measurements
- Compatible with multi-brand UPS systems





The INTELLIGENT PDU integrates Energy Intelligence functions into a single rack unit, providing clear and intuitive access to energy consumption data typical of technical environments for mission-critical applications. Thanks to the INTELLIGENT PDU, real-time operation is possible, offering valuable insights for accurate energy usage analysis. The wealth of information available allows the implementation of Business Continuity and Disaster Recovery strategies, including the ability to issue remote commands. This is made possible by the presence of a dedicated intelligent slot for optional communication cards featuring an embedded web server, compatible with major operating systems (Windows, macOS, and Linux). Upon request, supervision and analysis software is also available.

For more information, please contact us at sales@powermeitaly.it

Intelligent PDU	
Input voltage	220/230/240VAC
Inlet	IEC 16A with supplied cable
Power cable lenght	1,8m
Outlets	8 uscite x IEC 10A standard
LED	Fault LED - Power status LED
LCD	On/Off; input voltage and current; individual outlets current output, alarm indicators
Operating temperature	0-50°C
Relative humidity	0-95% HR (non condensing)
Physical	
Dimension DxWxH (mm)	250x430x44
Weight (kg)	~3,5

PowerMe reserves the right to modify technical specifications without prior notice.