



BATTERY			
Standard Model	Battery Type	12 V / 7-9 Ah	
	Numbers	20 pcs (18 - 20 pcs adjustable)	
	Typical Recharge Time	9 hours recover to 90% capacity	
	Charging Current (Max.)	2A	
	Charging Voltage	273 VDC ± 1% (Based on 20pcs batteries)	
INDICATORS			
LCD Display	UPS status, Load level, Battery level, Input/Output voltage, Discharge timer, and Fault conditions		
ALARM			
Battery Mode	Sounding every 4 seconds		
Low Battery	Sounding every second		
Overload	Sounding twice every second		
Fault	Continuously sounding		
PHYSICAL			
Standard Model	Dimension, DxWxH (mm)	815 x 250 x 826	815 x 300 x 1000
	Net Weight (kgs)	165	235
Humidity	0-95 % RH @ 0- 40°C (Non-condensing)		
Noise Level	Less than 58dB @ 1 Meter	Less than 60dB @ 1 Meter	
MANAGEMENT			
Smart RS-232/USB	Supports Windows Family, Linux, Unix, and MAC		
Optional SNMP	Power management from SNMP manager and web browser		
STANDARD REFERENCE			
Topology	VFI-SS-111 ref. EN 62040-3		
SAFETY and EMC	EN 60950 EN 62040-1 dir. 2006/95/EL; EMC: EN 62040-2 dir. 2006/95/CE		